

JIVA-8015/5815 Pro Series Specifications

| SPECIFICATIONS | JIVA-8015 | JIVA-5815 Pro |
|---------------------------------|---|--|
| Processor | Celeron 2.0 GHz | C7 1.0 GHz or up |
| Memory | 256 MB, DDR 266 (expandable to 2GB) | Default 256 MB , Expandable to 2GB DDR2 Memory |
| Video memory | 16~128 MB shared memory | 16MB~64MB shared memory |
| Display | 15" TFT, 1024 x 768, 200 nits | |
| Tilt adjustment | From 15° to 72.5° | |
| Touch sensor | PS/2 resistive panel standard (optional anti-scratch IR RS232 interface) | USB interface resistive Type (Anti-scratch IR type optional) |
| Touch resolution | 1024x1024, mouse emulation | |
| Expansion | | |
| Hard disk drive | Build-in 3.5", 40GB | |
| FDD | Option for USB interface | |
| Internal UPS | Yes. (Battery optional) | |
| Mounting option | Table top or wall mount | |
| Connectivity | | |
| Audio Line Output | Standard (with 2 speakers) | Standard (Audio Amp + Speakers option) |
| VGA Port | 1x | |
| Serial Port | 4x | |
| Parallel Port | 1x | |
| CR Port | 1x | |
| USB Port | 6x | 5x |
| PS/2 KB & MOUSE | YES | |
| LAN Port | 10/100 MHz base Ethernet | |
| Compact Flash Port | N/A | |
| OS Support | Microsoft Win 2000/XP Pro/WEPOS | Win 2000/CE.NET/WEPOS/XP Pro/Linux |
| Housing Color | Black | |
| Physical dimensions | | |
| Overall Dimensions w/ Slim Base | LCD @ 15°: 376mm(W) x 321mm(D) x 372mm(H) 14.8" x 12.6" x 14.6" LCD @ 72.5°: 376mm(W) x 306mm(D) x 295mm(H) 14.8" x 12.0" x 11.6" | |
| Weight | 9.2 kg (20.3 lbs) external power adaptor | 10.0kg (22.0 lbs.) |
| Electrical requirements | AC adaptor: Input 100~240V, output DC 12V/150W | AC adaptor: Input 100~240V, output DC 12V/80W |
| Storage Condition | -20°C +60°C; 10%RH ~ 80%RH; non-condensing; maximum wet bulb 28.9°C | |
| Operation Condition | 0°C~ +40°C; 20%RH~80%RH;non-condensing; maximum wet bulb 26°C | |
| Safety Certifications | PSU: ULVDE Terminal: FCC, CE (class A), RoHS | |
| Option peripherals | | |
| KP-100 | Mini footprint design security keyboard, 40 keys (24 programmable keys and ten key configuration) attachment. MSR, Smart card reader optional | |
| Total Keys | 40 keys | |
| Predefined keys | 0-9, +, -, ; total 16 keys | |
| OS support | Win98/2000/XP pro/WEPOS/NT/DOS | |
| Code Programmable | ASCII or SCAN code | |
| Programmable capacity | 1 to 255 characters per key | |
| Data Memory | 100 years data retention | |
| Power Source | 5V/200 mA max. from the PS/2 KB port | |
| MSR | ISO 7811 option 2 tracks(1&2 or 2&3), 3 tracks (1,2&3) with software programmable parameter or JIS II, KB interface | |
| Smart Card Reader | PC/SC 1.0; EMV level 1 | |
| SD-100 | Includes: MSR /Smart Card reader /iButton reader | |
| MSR | ISO 7811 option 2 tracks(1&2),3 tracks (1,2&3) or JIS II | |
| iButton Reader | Programmed by RS232 interface, output through PS/2 KB or RS232 interface | |
| Smart Card Reader | PC/SC 1.0; EMV level 1 | |
| SD-200 | In USB interface, Include: MSR/ Optical finger print sensor | |
| MSR | ISO 7811 option 2 tracks(1&2),3 tracks (1,2&3) | |
| Finger Print Sensor | Optical type: Detection area: 14.6x18.1 mm/ Resolution: 512 dpi x 8 bit gray scale/ OS support: 2000/XP/CE.NET/WEPOS/Linux | |
| BC-100U | Bar Code Card Reader, USB interface | |
| PD-302 | 2 by 20 VFD customer display, 5x7 dots matrix mounted on rear lower base | |
| PD-305 | 2 by 20 VFD customer display mounted on rear lower base | |
| PD-2501 | 11 mm 2 x 20 VFD display mounted on rear lower base | |
| PD-2602 | 9 mm 2 x 20 VFD display mounted on rear lower base, RS232 and USB interface option | |
| LM-6101 | 12.1" color LCD TFT (1024x768) as second display with rotatable bracket on rear lower base | |
| LM-6201 | 12.1" color LCD TFT (800x600) as second display with rotatable bracket on rear lower base | |

Information and specifications in this catalogue are subject to change without notice.

Posiflex Technologies, Inc.

6., Wu-Chuan Road, Wu-Ku, Taipei Hsien, Taiwan
TEL: +886.2.2299.1599 (Rep.) FAX: +886.2.2299.1819/1808
posiflex@posiflex.com.tw www.posiflex.com



01/23/2007 V.01

POSIFLEX
Your Success is Our Vision



Touch Terminal JIVA 8015/5815 Pro Series

State-of-the-Art Scalability for Integrated POS Solutions



Touch Terminal **JIVA** 8015/5815 Pro Series

- 15.1" dual backlit LCD panel-TFT active matrix
- ELO Accutouch or infrared Touch Sensor
- Spill-resistant architecture
- Power guard feature with software controlled power switch to prevent accidental shutdown of system
- Integrated UPS functionality protects the system from intermittent power failures
- Slim base stand
 - Optional UPS battery
 - Rear mount for 2nd display/pole display
 - HDD



Features



Integrated 2-in-1 MSR attachment and finger print sensor (SD-200)



Integrated bar-code card reader (BC-100U)



Integrated MSR, Smart Card Reader and 40-DynaKey programmable keyboard attachment (KP-100)



A patented finger release lever "Gear Lock" mechanism easily adjusts the LCD tilt angle from 15° to 72.5°



Security lock to prevent unauthorized access to data input/output devices



Interior



Wall Mount

Available peripherals



Cash Drawer (CR Series)



Second display



Customer display (PD-302)



Customer display (PD-2501)

Touch Terminal **JIVA** 8015/5815 Pro Series

Designed for hospitality, retail and vertical markets that require increased performance at the front-end workstation.